

P ▲ R ▲ D O X

Hybrid panel

MG5050+



COMMUNICATION

External voice module	Yes, with VDMP3 module
IP	Yes, with IP150 module
GPRS	Yes, with PCS module
GSM	Yes, with PCS module
Mobile Network	GPRS / GSM (with PCS module)
Programming	Installer, teacher and maintenance
Expansion bus	Yes, 4 wires

POWER CONSUMPTION

Power mode	AC
Voltage	16.5V
Amperage	1200mA
Battery support	Sí, 12V 4 ~ 7 Ah

AMBIENT

Operating temperature	0 °C ~ 50 °C
Use	Indoor
Maximum humidity	90%

CERTIFICATION

Grade	2
Normative	EN50131
Environmental class	II

PROGRAMMABLE OUTPUTS

Board	4
Maximum of PGMs	16
Telephone line	Sí

VIA RADIO

Frequency	433MHz / 868MHz
-----------	-----------------

ADDITIONAL FEATURES

Calendar	Sí
Software Update	Sí
StayD	Sí
Configuration and remote access	Yes

MATERIAL AND DIMENSIONS

Dimensions	190 x 102 mm
Net weight	170 g
Weight with packaging	220 g

ZONES

Maximum number of zones	32
Wired on-board zones	5
ATZ (Double zones)	Sí

PARTITIONS AND MEMORIES

Partitions	2
User codes	32

GENERAL INFORMATION

Type of Central	Hybrid
-----------------	--------

